

integre[®] pro

Laser Range

SINGLESPOT
**PATTERN
SCANNING**



Integre® pro Laser range

2 PHOTOCOAGULATION MODES

Integre® Pro laser range includes an extensive range of fully integrated systems, offering a wide array of parameters, tailored to the treatment of retinal pathologies.

Integre® pro

SingleSpot
technology



Integre® pro scan

Pattern Scanning
technology



SINGLE OR DUAL-WAVELENGTH LASER

Whether positioning focal treatment in the macular area, or performing PRP in the periphery, Integre® Pro lasers provide a comprehensive wavelength choice to treat a wide range of retinal conditions.^[5]

The following wavelength configurations are available:




GREEN CONFIGURATION (532 nm)



YELLOW CONFIGURATION (561 nm)



YELLOW-RED CONFIGURATION (561 nm and 670 nm)



HIGH PRECISION PERFORMANCE

The purpose-built Integre® Pro slit lamp, which channels the laser directly through the slit lamp optics for better visualization and optimal illumination, is optimized for use in the posterior segment.

All controls — **spot size**, **power**, **shot duration** and **micromanipulator** — are conveniently located, right at your fingertips.

UNIFORM ENERGY DISTRIBUTION

Integre® Pro's proprietary dual-mode laser cavity delivers uniform energy distribution across the full spot diameter, eliminating hotspots and achieving optimal, homogenous burns*.

Whether you are positioning focal treatment in the macular area, or performing PRP in the periphery, this dual-mode is a key design feature that enables you to achieve consistent, predictable treatment outcomes across a broad range of pathologies.





Image provided by Dmitri Yellachich, MD (Australia)

integre[®] pro



SingleSpot technology

Characterized by the use of long pulse durations (100–200 ms), Integre[®] Pro offers 3 customizable treatment modes for the implementation of thermal laser treatments :
Single, repeat and continuous.

integre[®] pro scan




Pattern Scanning technology

Characterized by the use of short pulse durations (10–20ms), Integre[®] Pro Scan offers many advantages over conventional photocoagulation in retinal treatments, especially for panretinal photocoagulation (PRP) procedures:

- Less heat diffusion to the retina and choroid, less damage to the retinal nerve fiber layer [1,2]
- Comfortable treatment is better tolerated by patients [3]
- Extremely fast treatment (full PRP in 1 session) [4].

The treatment mode can be delivered through customizable patterns for better adaptation to the treatment site:




DESIGNED WITH YOU IN MIND

A highly intuitive tablet and all-in-one laser/slit lamp interface that has been designed exactly with your needs in mind.

A user-friendly touchscreen interface allows for easy and rapid adjustment of treatment parameters, including laser power, pulse duration, pattern selection and pattern size.



An intuitive track pad enables easy navigation of the retina and adjustment of treatment settings and pattern characteristics.



Integre[®] pro

Laser Range

TECHNICAL SPECIFICATIONS

Laser Source	Solid-state laser diode and cavity
Wavelength	1 Yellow-red configuration: 561 nm and 670 nm 2 Yellow configuration: 561 nm 3 Green configuration: 532 nm
Power at the fiber port	Red: 1 W - Yellow: 1.5 W - Green: 1.5 W
Power at the cornea	Red: 50 – 1000 mW, Yellow: 50 – 1500 mW, Green: 50– 1500 mW
Aiming Beam	Red 635 nm, adjustable intensity
Magnification	6x, 10x, 16x, 25x, 40x
Electrical Requirements	100-240 VAC, 50/60 Hz, 800 VA
Cooling	Air cooled

	Integre [®] Pro	Integre [®] Pro Scan
Exposure Time	10 ms to 8.0 s	Pattern Scanning mode: 10 to 30 ms SingleSpot mode: 10 ms to 8.0 s
Spot Size	50 to 1000 µm, continuously variable	Pattern Scanning mode: 100 to 500 µm, continuously variable SingleSpot mode: 50 to 1000 µm, continuously variable
Repeat Mode	50 ms to 1.0 s	Pattern Scanning mode: N/A, SingleSpot mode: 50 ms to 1.0 s
Weight	32kg, 71 lbs. (laser only)	35kg, 77 lbs. (laser only)
Dimensions (HxWxD)	62 x 76 x 47 cm, 24 x 30 x 19 inches (laser only)	62 x 76 x 47 cm, 24 x 30 x 19 inches (laser only)

Specifications are subject to change without notice. Non contractual pictures.

© 2026. **Integre[®] Pro** and **Integre[®] Pro Scan** are trademarks of Ellex Medical Pty Ltd, a member of Lumibird Medical Division. All rights reserved.

BIBLIOGRAPHY

- 1- Jain A, Blumenkranz MS, Paulus Y et al. Effect of pulse duration on size and character of the lesion in retinal photocoagulation. Arch Ophthalmol. 2008; 126:78-85.
- 2- Yi-Ryeung Park, Donghyun Jee. Changes in Peripapillary Retinal Nerve Fiber Layer Thickness after Pattern Scanning Laser Photocoagulation in Patients with Diabetic Retinopathy. Korean J Ophthalmol 2014;28(3):220-225.
- 3- Hussaini S Al, Dodson PM and Gibson JM. Pain response and follow-up of patients undergoing panretinal laser photocoagulation with reduced exposure times. Eye. 2008; 22, 96-99
- 4- Muqit MM, Marcellino GR, Henson DB et al. Single-Session vs Multiple-Session Pattern Scanning Laser Panretinal Photocoagulation in Proliferative Diabetic Retinopathy. Arch Ophthalmol. 2010;128(5):525-533
- 5- Mainster MA. Wavelength selection in macular photocoagulation. Tissue optics, thermal effects, and laser systems. Ophthalmology.1986;93:952-958.



LASER CLASS 4
Nd:DPSS 532nm, 2W, 8s, CW (max)
Nd:DPSS 561nm, 2W, 8s, CW (max)
Nd:DPSS 670nm, 1.35W, 8s, CW (max)

LASER CLASS 2
Diode laser: 635nm, <1mW, CW

DANGER – LASER RADIATION AVOID EYE OR SKIN
EXPOSURE TO DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT per IEC60825-1:2014

CE
2797

UK
CA
0086

Manufacturer

Ellex Medical Pty Ltd
3-4, Second Avenue
Mawson Lakes, SA 5095 Australia
Tel: +61 (0)8 7074 8200
ISO 13485 : 2016

Headquarters

Lumibird Medical
1, rue du Bois Joli - CS40015
63 808 Courmon d'Auvergne – France
Tel: +33 (0)4 73 745 745

ELLEX
A brand of



LUMIBIRD[®]
MEDICAL

www.lumibirdmedical.com